

		Characteristics														
		Loading / Unloading		Speed (driven or non-driven conveyors)			Length		Mobility		Product Types To Convey			Dock Situation		
pewiSYS	Load and unload system	Loading	Unloading	High speed up to 55m/min	Standard speeds 6 -35m/min	Gravity/ Non powered	≥12.0m [40ft]	≤ 6.0m [20ft]	Mobile Chassis	Fixed Chassis	Box Handling	Bag Handling	Bulk Handling	Raised Loading Dock	Dockless	
		<b>Newland</b> <a href="#">Multi Telescopic Belt Conveyors</a>	✓	✓	✓	✓	N/A	✓	✓	✓	✓	✓	✓	✓	✓	✓
		<b>pewiGRAFLEX™</b> <a href="#">Gravity Flexible Roller Conveyor</a>	✓	✓	✗	✗	✓	✓	✓	✓	✗	✓	✗	✗	✓	✗
		<b>pewiFLEX™</b> <a href="#">Powered Flexible Roller Conveyor</a>	✓	✓	✗	✓	N/A	✓	✓	✓	✗	✓	✗	✗	✓	✗
		<b>pewiROLL™</b> <a href="#">Telescopic Roller Conveyor</a>	✗	✓	✗	✗	✓	✓	✓	✓	✗	✓	✗	✗	✓	✓
		<b>pewiLOAD™</b> <a href="#">Shuttle Conveyor</a>	✓	✗	✗	✓	N/A	✓	✓	✗	✓	✓	✓	✓	✗	✓
		<b>pewiROLLADER™</b> Telescopic Roller Conveyor with Automatic Telescopic Action	✓	✗	✗	✗	✓	✗	✓	✗	✓	✓	✗	✗	✗	✓
		<b>pewiVEHICLE™</b> <a href="#">Mobile Vehicle Loader. Belt Conveyor Combined with the pewiFLEX™/pewiGRAFLEX™</a>	✓	✓	✓	✓	N/A	✗	✓	✓	✗	✓	✗	✗	✗	✓
							Telescopic Action									